

# TECHNICAL SPECIFICATIONS

## AVANT 423

### LIFT CAPACITY

**550 kg**

### ENGINE POWER

**22 hp diesel**

### LIFT HEIGHT

**2.8 m**

### SPEED

**12 km/h**

## SPECIFICATIONS

<b>LENGTH</b>	2195 mm
<b>WIDTH (23X8.50-12 WHEELS)</b>	1050 mm*
<b>HEIGHT</b>	1980 mm
<b>WEIGHT</b>	1030-1080 kg
<b>STANDARD WHEELS</b>	23x8.50-12" grass/TR
<b>TRANSMISSION, DRIVE</b>	Hydrostatic
<b>PULLING FORCE</b>	700 kp
<b>DRIVE SPEED MAX.</b>	12 km/h
<b>AUX. HYDRAULICS OIL FLOW / PRESSURE</b>	34 l/min 185 bar
<b>HYDRAULIC OIL COOLER</b>	standard
<b>TURNING RADIUS INSIDE/OUTSIDE</b>	880 / 1970 mm
<b>MAX. LIFTING HEIGHT (WITH TELESCOPIC BOOM)</b>	2750 mm
<b>TIPPING LOAD</b>	550 kg
<b>ENGINE MAKE AND TYPE</b>	Kubota D902 Stage V
<b>ENGINE OUTPUT (ECE R120)</b>	16 kW (22 hp)
<b>MAXIMUM TORQUE</b>	56 Nm @ 2600 rpm
<b>FUEL</b>	Diesel
<b>PRODUCT NO:</b>	<b>A424315</b>

\*) Machine width with the road traffic light kit 1060 mm

## WIDTH

WHEEL SIZE	PROFILE	MACHINE WIDTH
5.70-12	tractor	930 mm*
23 x 8.50 - 12	tractor or grass	1050 mm*
23 x 10.50 - 12	tractor or grass	1090 mm

\*) Machine width with the road traffic light kit 1060 mm

## DIMENSIONS

